

What is claimed is:

1. Arrangement for a playground for children, which comprises a playhouse, a chute and a flight of steps, characterized by the fact that the arrangement is embodied as an internally hollow object (1), preferably of a synthetic material which, for instance can, be given the shape of a mountain top with a circumferential edge (2) at the bottom, which is mainly in one plane, and which rests on the ground, that the object (1) is embodied with windows (3) and one or more doorways (4) and that the internal hollow space (5) constitutes the playhouse, and that the chute (6) and the flight of steps (7) are embodied in the upper side of the object (1), and that there are means (11,14) to secure the object (1) to the surface of the ground.

2. Arrangement according to claim 1, characterized by the fact that the object (1) is made of glass fibre reinforced polyester or epoxy, which is cast over an internal mold (9) whereby a thin shell (10) is produced, which internal mold (9) is cast over a model of the finished object (1), to which has been applied a parting agent.

3. Arrangement according to claim 1, characterized by the fact that walking areas outside the chute (6) are embodied with a skid proof surface, which can be achieved by making the upper side of the model (8) smooth at the areas, where the object (1) is to be smooth, preferably a chute (6), and giving all other areas a skid proof surface.

4. Arrangement according to claim 1, characterized by the fact that the means (11,14) comprise a vertical or approximately vertical post or mast (11), for example of steel, which is carried through a hole (12) at the top of the object (1) and secured in the ground, for example in a foundation block (13), and of one or more anchors (14) carried through openings along the edge (2) and rammed down into the

ground.

5. Arrangement according to claim 4, characterized by the fact that the top of the mast (11) has a free height (h) above the top of the object (1), that a horizontal bar (16) is
5 secured to the mast (11) at one end (15) and at the other end is attached to a vertical post (17) which is rammed into or in other ways held solidly in the ground, whereby a frame is produced for a swing (18), and that furthermore there may to the upper end of the mast (11) be attached a rope (19), which
10 at its other end is fastened to a support, for instance a post (20), which is secured in the ground, thus constituting a ropeway.